

NEW SPECTRA INTERNATIONAL PAINTS

90 6th Street, Kensington, 7405

PH:021-5934774 email:sales@stirobond.co.za CELL:0836190502

DATA SHEET

STIRO BONDING SEALER

Composition

A styrene / acrylic copolymer emulsion.

Stiro bonding sealer has an exceptional water resistance, low dirt retention, alkali resistance and high pigment binding capabilities.

The product can be used across a wide range.

Scheming, screeding ,existing screeds to be raised,

Plastering, waterproofing, tile grouting bonding agent,

Painted on chipboard and wood for sealing purposes,

mixed into Paint to create a strong bond and excellent

for usage as a Cretestone sealer and a glue etc.

Surfaces should be clean, dry and sound. Existing

surface dirt, oil, tar, grease and mill film should

be removed prior to application.

Technical Data

Appearance: Homogenous

white liquid

Viscosity: 68.9 ku

ph: 7.88

T.S.C 28.18%

Drying time: +- 30 minutes

Safety and Storage

This product is water based and is non-toxic under normal conditions of use.

To ensure safe storage of this product. Containers should be well sealed to prevent evaporation and the formation of skin on the surface.

Packaging

1lt 2.5lt 5lt

20lt on request

Personal Safety Data

Warning

- 1) Causes skin irritation
- 2) Eye irritation

Precaution

The use of gloves and eye protection

First Aid

- 1) If in contact with skin wash with lots of hot soap and water
- 2) If in contact with eyes rinse with water continuously for min 10 minutes.
- 3) NOT FOR MEDICINAL USE